

## 20A SWITCH & OUTLET



SN 324



SN 418

SN 820

MODEL NO.	MODEL	AMPERE RATING (A)	POWER (W)	STANDARD	MEASUREMENT / UNIT	CTN PACKING
SN 324	20A DP SWITCH WITH NEON	20	5000 W	BS EN 60669 - 1	86 X 86 MM	100 / CARTON
SN 418	FUSE CONNECTION UNIT	20	5000 W	BS EN 60669 - 1	86 X 86 MM	100 / CARTON
SN 820	20A FLEX OUTLET/CONNECTION PLATE	20	5000 W	BS EN 60669 - 1	86 X 86 MM	200 / CARTON

	L,N,E
APPLICABLE WIRE RANGE*	1.0mm <sup>2</sup> - 6.0mm <sup>2</sup>

	L,N	E
INSULATION STRIPPING GAUGE	8 mm	8 mm

	L,N	E
APPROPRIATE TIGHTENING TORQUE	1.6Nm - 2.0 Nm	1.6Nm - 2.0 Nm

VOLTAGE RATING	250 V~
MATERIAL	UREA
CONDUCTING STRIP & CLIP	BRASS & COPPER
CONTACTS	SILVER
MOUNTING DEPTH	15 mm

